



## MOBILE HANDRAIL SYSTEM 70 M<sup>3</sup> TANKS

### IDEAL USAGE

Projects that require full access on top of the standard Baker Tanks:

- SVL (-SEP)
- SV (-SEP)
- SVC (-SEP)

## WEIGHT AND MEASURES

<b>Height:</b>	1,317 mm (service) 332 mm (transport)
<b>Width:</b>	2,512 mm (service) 2,512 mm (transport)
<b>Length:</b>	7,798 mm (service) 8,831 mm (transport)
<b>Weight:</b>	460 kg (approx.)

## MATERIAL

<b>Frame:</b>	galvanized steel (80 mm x 80 mm tube)
<b>Railing:</b>	galvanized steel (40 mm x 40 mm tube)
<b>Forklift pockets:</b>	galvanized steel (200 mm x 80 mm x 4 mm tube)

## FEATURES

<b>Installation:</b>	Railing is installed at Baker site prior to transportation. Installation on site requires only fold up of railing.
<b>Forklift pockets:</b>	2 forklift pockets for easy installation on top deck of tank
<b>Ladder:</b>	Fold down ladder for easy access to top deck of tank from platform

## QUALITY AND SAFETY

- Platform build according to EN-ISO 14122-2,3: safety of machinery - working platforms, guardrails
- Scheduled QMS inspections

