

Data sheet

COMPRESSOR 23 M³ DIESEL SKID 12 BAR NAK STAGE III

IDEAL USAGE

Ideal for projects with various applications where reliable compressed air supply is required.

APPLICATIONS

- Powering pneumatic tools, air supply for blasting operations or temporary process air.
- Reliable compressed air in remote locations without a permanent power supply thanks to mobility.
- Use in building and construction work where a constant supply of compressed air is required.



COMPRESSOR

Manufacturer and Model	KAESER	M250
Working pressure	7 / 10 bar	
Capacity	25 / 23 m ³ / min	
Undercarriage	Skid	

ENGINE

Manufacturer and Model engine	Mercedes	OM926LA
Emission Standard	Euro Stage IIIB	
Power	2115 kW	

ELECTRICAL FEATURES

Connections	3x claw 3/4" 1x Camlock 2"
-------------	-------------------------------

WEIGHT AND DIMENSIONS

Length	4230 mm
Width	1980 mm
Height	2120 mm
Weight	3000 kg
Capacity Fuel Tank	350 L
Capacity AdBlue Tank	40 L

FUEL CONSUMPTION

100% Load Prime	43 L/h
100% Load Prime (AdBluetank)	0.4 L/h

AUTONOMY

100% Load Prime	8 uur
100% Load Prime (AdBluetank)	8.1 uur

TYPICAL SOUND PRESSURE

dBa @ 1 m	80 dB
-----------	-------

COMMUNICATION AND CONTROL

- Featuring:
- Digital control panel
 - Adjustable pressure
 - Operating hours
 - Alarms
 - Maintenance
 - Bund alarm
- Readable data:
- GPS
 - Fuel level alarm
 - Engine running hours
 - Alarms and warnings

Technical drawing

